

## 1. 2-door Coupe

### A: DIMENSIONS

Model				2200	2500
				AWD	AWD
				L	RS
Overall length		mm (in)		4,375 (172.2)	
Overall width		mm (in)		1,705 (67.1)	
Overall height		mm (in)		1,410 (55.5)	
Compartment	Leg room	Front Max.	mm (in)	1,094 (43.1)	
		Rear Min.	mm (in)	825 (32.5)	
	Head room	Front	mm (in)	995 (39.2)	
		Rear	mm (in)	933 (36.7)	
	Shoulder room	Front	mm (in)	1,335 (52.6)	
		Rear	mm (in)	1,325 (52.2)	
Wheelbase		mm (in)	2,520 (99.2)		
Tread	Front	mm (in)	1,460 (57.5)	1,470 (57.9)	
	Rear	mm (in)	1,450 (57.1)	1,460 (57.5)	
Minimum road clearance		mm (in)	145 (5.7)		

### B: ENGINE

Model		2200	2500
Engine type		Horizontally opposed, liquid cooled, 4-cylinder, 4-stroke gasoline engine	
Valve arrangement		Overhead camshaft type	
Bore x Stroke	mm (in)	96.9 x 75.0 (3.815 x 2.953)	99.5 x 79.0 (3.917 x 3.110)
Displacement	cm <sup>3</sup> (cu in)	2,212 (135.0)	2,457 (149.9)
Compression ratio		10.0	9.7
Firing order		1 — 3 — 2 — 4	
Idle speed at Park/Neutral position	rpm	700 ± 100	
Maximum output	kW (HP)/rpm	106 (142)/5,600	123 (165)/5,600
Maximum torque	N.m (kg-m, ft-lb)/rpm	202 (20.6, 149)/3,600	225 (22.9, 166)/4,000