



ILLUSTRATED SYMBOLS (Refer to the illustration)

Illustrated symbols ① to ⑨ are designed as thumb tabs to indicate the chapter's number and content.

- ① General information
- ② Periodic inspection and adjustment
- ③ Chassis
- ④ Power train
- ⑤ Engine
- ⑥ Cooling system
- ⑦ Fuel injection system
- ⑧ Electrical
- ⑨ Specifications

Illustrated symbols ⑩ to ⑯ are used to identify the specifications which appear.

- ⑩ Filling fluid
- ⑪ Lubricant
- ⑫ Tightening torque
- ⑬ Wear limit, clearance
- ⑭ Engine speed
- ⑮ Special tool
- ⑯ Electrical data (Ω , V, A)

Illustrated symbols ⑰ to ⑳ in the exploded diagram indicate grade of lubricant and location of lubrication point.

- ⑰ Apply locking agent (LOCTITE®)
- ⑱ Apply Yamabond No.5®
- ⑲ Apply engine oil
- ⑳ Apply gear oil
- ㉑ Apply molybdenum disulfide oil
- ㉒ Apply brake fluid
- ㉓ Apply wheel bearing grease
- ㉔ Apply low-temperature lithium-soap-based grease
- ㉕ Apply molybdenum disulfide grease
- ㉖ Apply silicone grease
- ㉗ ESSO beacon 325 grease or Aeroshell grease #7A
- ㉘ Use new one